



# MILLGRAIN MACHINERY INDUSTRIES



**BUILD  
YOUR  
FUTURE**



# MILLGRAIN MACHINERY INDUSTRIES

## STITCHING CONVEYOR



Model	MG-BC-8000	MG-BC-8002
No. of Needle	Single	Double
Thread	Two	Four
Seam Type	Double Thread Chain Stitch	Four Thread Chain Stich
Production Capacity	700-800 Bags/hr	700-800 Bags/hr
Stitch Length Adjustment	5-9 mm	5-9 mm
Needle Size	DR x 2#26 (Groz-Beckert)	DR x 2#26 (Groz-Beckert)
Thread Type	Cotton or Synthetic	Cotton or Synthetic
Sewing Capacity	Up to 18 mm	Up to 18 mm
Bag Material	PP Woven Fabric, PP Laminated Woven Fabric, & Paper	PP Woven Fabric, PP Laminated Woven Fabric, & Paper
Start / Stop	Photo / Switch	Photo / Switch
Thread Cutter Type	Electro - Pneumatic Thread Cutter/	Electro - Pneumatic crape Trape/pp Tape Cutter
Air Pressue	6 kg.	6kg.
Air Consumption	250 Lit./Min.	250 Lit./Min.
Photo Cell Range	Up to 500 mm.	Up to 500 mm.
Lubrication System	Manual Oil Feed & Oiler System	Manual Oil Feed & Oiler System
Drive Motor	For Sewing Head 0.5 H.p., 3 phase conveyor 1 H.P., 3 phase	For Sewing Head 0.5 H.p., 3 phase conveyor 1 H.P., 3 phase
Conveyor	Slat or Belt Type	Slat or Belt Type
Height Adjustment	300-950 mm (sewing Machine)	300-950 mm (sewing Machine)



## BAG CLOSING MACHINE



Model : **MGM BC 70 ( Single Row)**  
**MGM BC 72 (Double Row)**  
Easy to operate bag closing machine

- + MGM - BC 70/72 Series Sewing Heads, used in combination with a line of Bag Closing Columns & Conveyor.
- + To Close filled bags with Rice, sugar, Flour, Grains, Fertilizer, pet Food Chemicals, Seed, Coffee, Salt, Minerals and hundreds of other product.

Model	MG-BC-70	MG-BC-72
Needle	One	Two
Thread	Two	Four
Seam Type	Double Thread Chain Stitch	Four Thread Chain Stich
Production Capacity	700-800 Bags/hr	700-800 Bags/hr
Stitch Length Adjustment	6.5-10 mm	
Maximum Speed	1800 R.P.M	
Thread Type	Cotton or Synthetic	
Production Capacity	500 – 600 Bags/Hr.	
Bag Material	PP Woven- Fabric, PP Laminated Woven Fabric, jute, Hassian & Paper	
Needle Size	DR X 2 # 28 (orange make)	
Thread Cutter Type	Mechanical Thread Cutter	
Lubrication System	Manual Oil Feed & Oiler System	
Sewing Capacity	Up to 18 mm	
Drive Motor	Sewing M/c	0.5 H.p., 3 phase , 1350 RPM
	Conveyor	1 H.p., 3 phase , 1350 RPM
Conveyor	Slat or Belt Type	
Conveyor Dimension	2000 mm x 390 mm x 275 mm (*customized option)	
Height Adjustment	300-950 mm (sewing Machine)	



## **Millgrain Machinery Industries**

**Reg Off: No. 312, Arani Main Road, Thuthipattu, Vellore-632011, Tamilnadu, India**

**Mobile: (+91) 8778201289 / (+91) 8105566637**

**E-mail: [millgrain2000@gmail.com](mailto:millgrain2000@gmail.com)  
[kumarvinayagam79@gmail.com](mailto:kumarvinayagam79@gmail.com)**

**Website: [www.millgrain.in](http://www.millgrain.in)**